

SSP-502-65 Continuous Roll Conductive Silicone Elastomer

PRODUCT DESCRIPTION

The SSP502-65 is a 65 durometer nickel coated graphite filled elastomer produced in continuous rolls. This product can be supplied in thickness between 0.015" and 0.062" thick and widths up to 15 inches. The data below was generated using ASTM test methods and procedures. The data for volume resistivity is measured from the finished roll.

DATA	Typical Values
Shore A (58- 68 range)	65
Tensile psi (200 minimum)	240 psi
Elongation % (200 minimum)	530%
Tear "B" ppi (35 min)	60
Specific Gravity (Report)	1.93
Volume Resistivity ohm / cm	0.07 ohm /cm
Color	Dark Gray
Thermal Stability Range	-55°C - 200°C

HANDLING & SAFETY

MSDS information is available on request.



**Seal & Design
Able Division**
5533 Steeles Avenue West Unit 11
Toronto, Ontario M9L 1S7
Ph: (416) 741-0750
Gasket@AbleSealAndDesign.com



**Seal & Design
Corporate Headquarters**
4015 Casilio Parkway
Clarence, NY 14031
Ph: (716) 759-2222
Info@SealAndDesign.com
www.SealAndDesign.com



**Seal & Design
Higbee Division**
6741 Thompson Rd N
Syracuse, NY 13221
Ph: (315) 432-8021
Sales@Higbee-Inc.com

Because we cannot foresee or control varied conditions, under which this information and our materials may be used, we do not guarantee the applicability or accuracy of this information or the suitability of our materials for their specific purposes. This material is provided without warranty, either expressed or implied, of fitness for a specific purpose or nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents.