




Corporate Headquarters
 4015 Casilio Parkway
 Clarence, New York 14031
 Ph: 716-759-2222 • Fax 716-759-6425



Canadian Division
 5511 Steeles Ave West • Unit 5
 North York, Ontario M9L 1S7
 Ph: 416-741-0750 • Fax: 416-741-0230

PTFE

INERTEX® UHF SEALANT



(download PDF)

INERTEX® UHF Joint Sealant looks and feels different from other Joint Sealant products. It is smooth and flexible with an exceptionally uniform texture and density. Under the surface is a microscopic structure that makes this remarkable material the strongest, most versatile sealant available today. It is manufactured by a patented process that produces a Uniform and highly fibrillated microstructure. It is a FDA suitable and comes with a full paper covered self-adhesive backing that makes installation simple.

Product Benefits:

- Soft and compressible under low bolt loads. Excellent for use on plastic, FRP, odd-shaped, and large flanges
- Excellent for use on damaged or imperfect surfaces. Can also be used on worn or used metal gaskets
- Self-aligning. Simple to use
- Contains no silicones and is suitable for paint booth applications

Size	Standard Length (ft/spool)	Size	Standard Length (ft/spool)
1 mm	100, 1000	1/2"	15, 30, 150
1/8"	100, 1000	5/8"	15, 30, 150
3/16"	75, 750	3/4"	15, 30, 50, 150
1/4"	50, 100, 500	1"	15, 30, 75
3/8"	25, 50, 250	2"	39