



Leader Ring Type Joint RX

Ring Type Joint Gaskets



DESCRIPTION

Leader ring type joint flange gaskets (RTJ gaskets) are used in applications that involve extreme pressures and high temperatures. All Leader ring type joint gaskets are manufactured in compliance with API-6A and ANSI B16.2 specifications. Whether you are looking for a standard ring type joint gasket or custom design assemblies, our team of application engineers have the product and application know-how to find the right solution for your specific application.

APPLICATION

Ring Joint gaskets are widely used between pipeline flanges, valves and pressure vessels in the Oil & Gas industry; Withstand high pressure situations up to 400 bar (pending on flange

construction and rating); Style RX gaskets are suitable for ASME B16.5 flanges up to 2500 lbs. API 6A type 6B flanges can withstand a pressure up to 5000 psi.

CHEMICAL COMPATIBILITY

Ring Joint gaskets are widely used between pipeline flanges, valves and pressure vessels in the Oil & Gas industry; Withstand high pressure situations up to 400 bar (pending on flange construction and rating); Style RX gaskets are suitable for ASME B16.5 flanges up to 2500 lbs. API 6A type 6B flanges can withstand a pressure up to 5000 psi.

DELIVERY OPTIONS

RX shaped RTJ gaskets are available in ring numbers RX20 up to RX215. Customer specific gaskets can be

manufactured upon request. Other materials are also available, please refer to table

TEMPERATURE

Ring Joint gaskets are widely used between pipeline flanges, valves and pressure vessels in the Oil & Gas industry; Withstand high pressure situations up to 400 bar (pending on flange construction and rating); Style RX gaskets are suitable for ASME B16.5 flanges up to 2500 lbs. API 6A type 6B flanges can withstand a pressure up to 5000 psi.

SEALING CHARACTERISTICS

- Non blow-out type

TECHNICAL DATA

Gasket required flange roughness [Ra micron]	1,6 max.
Gasket required flange roughness [RMS]	63 max.

METALLIC MATERIALS

	Identification	Color coding	Temperature Range
	ASME B16.20	ASME B16.20	Degrees C.
Carbon Steel	CRS	Silver	- 25 / + 500
SS304(L)	304(L)	Yellow	- 200 / + 900
SS316(L)	316(L)	Green	- 100 / +550
SS321	321	Turquoise	-200/+550
SS347	347	Blue	-200/+550
Duplex (ASTM A182-F51)	31803	No colour	-60/+300



METALLIC MATERIALS

Avesta 254 SMO (6Mo)	31254	No colour	-100/+550
Carpenter 20 CB3	A20	Black	-100/+500
Nickel 200	NI200	Red	-100/+450
Nickel 201	NI201	Red	-100/+550
Monel® / Alloy 400	MON	Orange	-50/+500
Inconel® / Alloy 600	INC600	Gold	-100/+650
Inconel® / Alloy 625	INC625	Gold	-100/+800
Inconel® / Alloy X-750	INX	No colour	-100/+700
Incoloy® / Alloy 800	IN800	White	-100/+550
Incoloy® / Alloy 825	IN825	White	-200/+800
Hasteloy® / Alloy B2	HAST B	Brown	-100/+500
Hasteloy® / Alloy C276	HAST C	Beige	-100/+600
Titanium	TI	Purple	-100/+350
Zirconium	ZIRC	No colour	-50/+900



**Seal & Design
Able Division**

5533 Steeles Avenue West Unit 11
Toronto, Ontario M9L 1S7
Ph: (416) 741-0750
Gasket@AbleSealAndDesign.com



**Seal & Design
Corporate Headquarters**

4015 Casilio Parkway
Clarence, NY 14031
Ph: (716) 759-2222
Info@SealAndDesign.com
www.SealAndDesign.com



**Seal & Design
Higbee Division**

6741 Thompson Rd N
Syracuse, NY 13221
Ph: (315) 432-8021
Sales@Higbee-Inc.com