

RG-N100

Thermoseal RG-N100 is a nitrile butadiene rubber, reinforced cellulose fiber and mineral filler general purpose gasket material. Continuous roll lengths allow efficient and economical fabrication with high speed die cutting equipment. Its low density provides good conformability in sealing fuels, oils, and water in applications such as automobile water pumps, miscellaneous cover gaskets, and many small engine applications. RG-N100 is suitable for applications with intermittent operating temperatures up to 350° F (177° C).



Ref. Thickness of Measured Values	0.031" (0.8mm)
Density ASTM F1315	62 lbs/ft ³ (1.00 g/cm ³)
Compressibility ASTM F36J	20 - 40%
Recovery ASTM F36J	minimum 30%
Tensile Strength ASTM F152	minimum 1015 psi (7 MPa)
Fluid Resistance	
After immersion in Fuel B	
Weight Increase	maximum 40%
Thickness Increase	maximum 10%
After immersion in Oil IRM903	
Weight Increase	maximum 50%
Thickness Increase	maximum 10%
Binder Type	Nitrile Butadiene Rubber
ASTM F104 Line Call Out	F729900E99M9

For Additional Information Call Toll Free 1.800.990.7325 or email info@thermosealinc.com

Thermoseal Inc. 2350 Campbell Rd., Sidney, Ohio 45365 United States, Tel: (937) 498-2222, Fax: (937) 498-4911
www.thermosealinc.com, email: info@thermosealinc.com



**Seal & Design
Corporate Headquarters**

4015 Casilio Parkway
 Clarence, NY 14031
 Ph: (716) 759-2222
 Info@SealAndDesign.com
www.SealAndDesign.com



**Seal & Design
Higbee Division**

6741 Thompson Rd N
 Syracuse, NY 13221
 Ph: (315) 432-8021
 Sales@Higbee-Inc.com



**Seal & Design
Able Division**

5533 Steeles Avenue West Unit 11
 Toronto, Ontario M9L 1S7
 Ph: (416) 741-0750
 Gasket@AbleSealAndDesign.com